




Ambiance 24V

Ambiance LED strips can be used to create effective indirect general lighting or atmospheric accent lighting. The stepless control of the LED strip's white colour temperature from warm to cold enables a wide variety of choices for general lighting. The IP20 and IP65 models of the strip enable it to be mounted in many different places. With the high level of luminous flux, the strips are particularly suitable for surface reflection to create non-glare indirect lighting in a room. A strip can be mounted on the window jamb or on the back of furniture, paintings and mirrors. An LED strip mounted on the underside of steps or on handrails provides extra safety on staircases. The IP65 strip is suitable for wet spaces. It can be mounted beneath kitchen cabinets, or above them for the soft reflection of light from the ceiling. The high luminous flux and excellent colour rendering qualities enable a wide variety of uses in public spaces. The series also includes a ready-to-use IP20 package, containing the LED strip and all the necessary components



- IP20: Uncoated LED strip, 24 V.
- IP65: UV-protected silicone-coated LED strip, 24 V.
- Protection class III.
- 5 m reel, 2 m connecting cable.
- The strip is equipped with double-sided adhesive tape. Airam's broad Slimline profile range is recommended for underside installations. Check the compatibility table for suitable installation profiles.
- Stepless control of colour temperature from 2,200 to 6,500K. CRI > 90 / Ra > 90.
- MacAdam 3 SDCM.
- The LED strip control requires a 24V direct voltage source, LED controller (4016037) and remote control (4016038). The ready-to-use LED package contains all the required components.
- IP20 and IP65.
- E.g. 4,000K 1,800 lm/m, 12W/m.
- Ambient temperature range IP20: 0 ... 25°C.
- Ambient temperature range IP65: -15 ... 25°C:
- Rated lifetime: L70 50,000 h (Ta 25°C).
- Project-specifically available as a Casambi solution, cut to measure and installed inside a profile, when necessary.
- Accessories (IP20):
- Ambiance quick connector IP20 4146527, for connecting two previously cut Ambiance strips.
- Ambiance quick connector IP20 2MLJ 4146528, for connecting two previously cut Ambiance strips with a two-metre connecting cable. Suitable for purposes such as crossing over windows or kitchen hoods.



4146525 IP20



4146526 IP65



A quick connector 4146527 designed for connecting two Ambiance IP20 LED strips quickly and easily.



The Ambiance series also includes a ready-to-use IP20 package, containing the LED strip and all the necessary components.

• In stock

Ambiance 24V IP20

NO.	CODE	W
• 4146525	A2LSAC P20 12W/m TW 5m	60

Ambiance 24V IP65

NO.	CODE	W
• 4146526	A2LSAD IP65 12W/m TW 5m	60

Ambiance 24V Kit IP20

NO.	CODE	W
• 4146610	A2LSAE Ambiance 24V Kit IP20 60W TW 5m	60

Ambiance 24V accessories

NO.	CODE
• 4146527	A2ACAG Connector IP20 A
• 4146528	A2ACAH Connector IP20 2meter