





Blitz M Ceiling

Blitz Sq M Ceiling is a surface-mounted ceiling luminaire with a rectangular design. The luminaire is suitable for indoor and outdoor use. Integrated LED. High-quality surface treatment, stainless steel screws.

- Aluminium housing and transparent glass diffuser.
- Anthracite, silver, black and white.
- Protection class I.
- Surface mounting.
- Not linkable, 3 x 2.5 mm².
- Installation height 0.5–4 m.
- Luminous flux 1665–1750 lm.
- Connected load 18W.
- IP65.
- IK07.
- On/off.
- Ambient temperature range -25 ... 25 °C
- Rated lifetime L70 50,000 h (Ta25°C).
- Power source service life 50,000 h.
- AN = anthracite, SI = silver, BK = black, WH = white.
- Also available in Corten colour on a project-specific basis.



By order

Blitz M Ceiling anthracite

NO.	CODE	W	LM
4511546	B5BZNA IP65 18W/830 GLC ANT	18	1665
4511551	B5BZOA IP65 18W/840 GLC ANT	18	1750

Blitz M Ceiling black

NO.	CODE	W	LM
4511548	B5BZNC IP65 18W/830 GLC BK	18	1665
4511553	B5BZOC IP65 18W/840 GLC BK	18	1750

Blitz M Ceiling white

NO.	CODE	W	LM
4511549	B5BZND IP65 18W/830 GLC WH	18	1665
4511554	B5BZOD IP65 18W/840 GLC WH	18	1750

Blitz M Ceiling silver

NO.	CODE	W	LM
4511547	B5BZNB IP65 18W/830 GLC SI	18	1665
4511552	B5BZOB IP65 18W/840 GLC SI	18	1750