





## Cestus H Eye

The wall-mounted Cestus H Eye luminaire with an aluminium housing and polycarbonate diffuser is designed for demanding applications where high impact resistance is required. It is suitable for use on exterior walls of residential buildings and it can be installed on both new and renovated buildings. The luminaire is available as models with an integrated LED and an E27 base.

- Die-cast aluminium body and polycarbonate diffuser.
- White and anthracite.
- Protection class I.
- Surface mounting on the wall or the ceiling.
- Linkable, 3 x 2.5 mm<sup>2</sup>, spring terminal blocks.
- Knockouts for surface wiring.
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- MacAdam 3 SDCM.
- IP65.
- IK10.
- Fixed LED 20W / 800 lm.
- LED-lamp A60 E27 max. 11W, not included.
- Ambient temperature range -25 ... 25 °C.
- Rated lifetime L70 50,000 h (Ta25°C).



• In stock

### Cestus H Eye

NO.	CODE	W	LM
• 4510225	A5CEAF IP65 IK10 20W/840 PCO ANT H	20	830
• 4510224	A5CEAE IP65 IK10 20W/840 PCO WH H	20	830

### Cestus H Eye E27

NO.	CODE
• 4510234	A5CEBF IP65 IK10 E27 PCO ANT H
• 4510233	A5CEBE IP65 IK10 E27 PCO WH H