



## Eval

The slimline Eval luminaire range is designed for offices and other public spaces. The luminaires are equipped with a matt anti-glare shield. The luminaire can be surface mounted or suspended using a wire-suspension fixture that is sold separately. The standard range includes two colour temperatures and efficacies.

- Steel housing, a matt aluminium anti-glare shield.
- White RAL 9003.
- Protection class I.
- Linkable, 3 x 2.5 mm<sup>2</sup>, Dali-2 models 5 x 2.5 mm<sup>2</sup>.
- Installation height 2–4 m.
- Fixed LED: 33–51 W, 2800–4100 lm.
- Colour temperatures 3000 K and 4000 K CRI > 80 / Ra > 80.
- MacAdam 3 SDCM.
- IP20.
- The standard range includes on/off and Dali-2 models.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 100 000 h (Ta25°C).
- Rated lifetime L80 65 000 h (Ta25°C).
- Power source service life 50 000 h.
- Wire-suspension fixture 4107113 and 4146595 are available as an accessories.
- WH = white, DA2 = Dali-2, AL = aluminium, MA = matt.
- Also available as Casambi, 1–10 V and Switch Dim solutions, and Tunable White model on a project-specific basis. CRI > 90 / Ra > 90 available by special order. Also available with various connecting wire solutions, a high-polish visor, and a 1500 mm frame. A 4800 lm luminous flux set is also available by special order.



Vaijeriripustus.



### By order

#### Eval

NO.	CODE		W	LM
4289843	D2EVAA	IP20 33W/830 AL MA WH	33	2800
4289844	D2EVAB	IP20 33W/840 AL MA WH	33	2800
4289845	D2EVBA	IP20 51W/830 AL MA WH	51	4100
4289846	D2EVBB	IP20 51W/840 AL MA WH	51	4100

#### Eval Dali

NO.	CODE		W	LM
	D2EVAA-DALI	IP20 33W/830 DA2 AL MA WH	33	2800
	D2EVAB-DALI	IP20 33W/840 DA2 AL MA WH	33	2800
	D2EVBA-DALI	IP20 51W/830 DA2 AL MA WH	51	4100
	D2EVBB-DALI	IP20 51W/840 DA2 AL MA WH	51	4100