





## Fresa Pro

Fresa Pro is a versatile luminaire with improved features that make it even more flexible. The luminaire has a switch that allows you to change the luminous flux of the luminaire between four different options. In addition, the energy efficiency and installability of the luminaire have been improved. Throughwired Fresa Pro is suitable for installation in industrial and parking halls and shelters. The material of the luminaire is durable and high-quality polycarbonate and the latches are stainless steel. The luminaire can be attached to the ceiling, wall or suspended with the accessories included.

- Polycarbonate body and diffuser (PCO).
- Grey.
- Protection class I.
- Surface mounting on a wall or ceiling, suspension mounting possible with accessories.
- Throughwired 5 x 2.5 mm<sup>2</sup>.
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK08.
- Integrated LED, efficacy can be adjusted on the luminaire.
  - 1200 mm: 40 W / 6000 lm; 34 W / 5100 lm; 28 W / 4200 lm; 22 W / 3300 lm.
  - 1500 mm: 60 W / 9000 lm; 51 W / 7650 lm; 42 W / 6300 lm; 33 W / 4950 lm.
- MacAdam 5 SDCM.
- On/off.
- Ambient temperature range -20 ... 40 °C.
- Rated lifetime L70 50,000 h (Ta25°C).



• In stock

### Fresa Pro

NO.	CODE		W	LM
• 4338594	A3FRPA	1200 IP65 40W/840 6000lm PCO	40	6000
• 4338595	A3FRPB	1500 IP65 60W/840 9000lm PCO	60	9000

## Versatile Fresa Pro

The luminaire has a switch that allows you to change the luminous flux between four different options. The energy efficiency and installability of the luminaire have been improved.