


Fresa Pro




Fresa Pro is a versatile luminaire whose features make it a flexible solution for a wide range of lighting requirements. The luminaire is equipped with a switch that allows the luminous flux to be selected from four different output levels. Easy installation makes it a practical solution for professional applications. Throughwired Fresa Pro is suitable for installation in industrial and parking halls and shelters. The material of the luminaire is durable and high-quality polycarbonate and the latches are stainless steel. The luminaire can be attached to the ceiling, wall or suspended with the accessories included.

- Polycarbonate body and diffuser (PCO).
- Grey.
- Protection class I.
- Surface mounting on a wall or ceiling, suspension mounting possible with accessories.
- Throughwired 5 x 2.5 mm^2.
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK08.
- Integrated LED, efficacy can be adjusted on the luminaire.

  1200 mm: 40 W / 6000 lm; 34 W / 5100 lm;
  28 W / 4200 lm; 22 W / 3300 lm.
  1500 mm: 60 W / 9000 lm; 51 W / 7650 lm;
  42 W / 6300 lm; 33 W / 4950 lm.
- MacAdam 5 SDCM.
- On/off.
- Ambient temperature range -20 ... 40 °C.
- Rated lifetime L70 50,000 h (Ta25°C).







• In stock

Fresa Pro

NO.	CODE	W	LM
• 4338594	A3FRPA 1200 IP65 40W/840 6000lm PCO	40	6000
• 4338595	A3FRPB 1500 IP65 60W/840 9000lm PCO	60	9000