






Futura Max

An energy-efficient industrial luminaire for unheated warehouses, freezer rooms and premises with high temperatures. Resistant to fluctuations in the ambient temperature. Excellent impact strength. Wall brackets and lighting track brackets are available as accessories. Please also read about the other luminaires in the Futura range: Futura PC, Futura Abs ja Futura NB.

- Polycarbonate housing and opal diffuser (PC), stainless steel latches.
- Grey.
- Protection class I.
- Surface mounting.
- Throughwired 5 x 2.5 mm².
- Installation height 2–10 m.
- Integrated LED:
 - 1450 x 98 mm: 33 W / 4800 lm.
 - 1172 x 145 mm: 51 W / 8200 lm.
 - 1452 x 145 mm: 71 W / 11 300 lm.
- Colour temperature 4000 K. CRI > 80 / Ra > 80.
- MacAdam 3 SDCM.
- IP66.
- IK10.
- On/off.
- Ambient temperature range -40 ... 60 °C.
- Rated lifetime L80 50 000 h (Ta60°C).
- Power source service life 50 000 h.



4338544



By order

Futura Max

NO.	CODE		W	LM
4338544	T3FMBA	1500 IP66 IK10 4800lm/840 PCO Max	33	4800
4338545	T3FMBB	1200 IP66 IK10 8200lm/840 PCO Max	51	8200
4338546	T3FMBC	1500 IP66 IK10 11300lm/840 PCO Max	71	11300