



Highbay Lite

Designed for high, open halls and warehouses, Highbay Lite is a cost-efficient high-bay luminaire made of durable, high-quality materials. The luminaire is equipped with an integrated junction box and a carabiner, to ensure quick and easy suspension mounting and connection to other luminaires. Surface mounting is possible with a separately ordered mounting bracket. The luminaire can be tilted + - 45 degrees when surface mounted, in which case the product can also be mounted on sloping ceiling surfaces.

- Die-cast aluminium body and UV-protected, impact-resistant polycarbonate lenses.
- Lens optics, opening angle of 90 degrees.
- Black, RAL9017.
- Protection class I.
- Linkable, 5 x 2.5 mm².
- Suspension mounting with a chain or wire, surface mounting with an installation bracket (4338514), available by separate order.
- Installation height 5–12 m.
- Colour temperature 4,000 K. CRI >80 / Ra > 80.
- IP65.
- IK08.
- Fixed LED 100 W / 13 000 lm; 150 W / 20 000 lm; 240 W / 32 000 lm.
- MacAdam 5 SDCM.
- 1-10V.
- Ambient temperature range -30 ... 50 °C.
- Rated lifetime L70 100,000 h (Ta25°C).
- Power source service life 100,000 h (Ta25°C).
- Various extension cables are available on a project-specific basis.



• In stock

Highbay Lite




SNRO	KOODI		W	LM
• 4338500	A3HECA	IP65 100W/840 WB 1-10V PCC	100	13000
• 4338501	A3HECB	IP65 150W/840 WB 1-10V PCC	150	20000
• 4338502	A3HECC	IP65 240W/840 WB 1-10V PCC	240	32000



4338500 / 4338501



4338500



Surface mounting with ceiling bracket (4338514).