




Kappa H

Kappa H is a wall luminaire suitable for indoor and outdoor use. With its rounded corners, this elegant luminaire blends in with the décor in both new and renovated buildings. Kappa H model has an anti-glare shield. It comes with an integrated LED and two colour temperatures. A light source with an E27 base can be ordered separately. High-quality surface treatment.



- Aluminium housing and frosted glass diffuser.
- Anthracite, silver, black and white.
- Protection class I.
- Surface mounting.
- Not linkable, 3 x 2.5 mm².
- Installation height 0.5–4 m.
- Integrated LED 9W / 830 510lm, 840 530 lm.
- Led lamp max. 11 W A60 E27, not included.
- Lamp recommendations: Airam Frost led -range.
- Colour temperatures of the integrated LEDs 3,000 K and 4,000. CRI > 80 / Ra > 80.
- IP55.
- IK03.
- On/off.
- Ambient temperature range -25 ... 25 °C
- Rated lifetime L70 50,000 h (Ta25°C).
- Power source service life 50,000 h.
- AN = anthracite, SI = silver, BK = black, WH = white.



By order

Kappa H 830

NO.	CODE	W	LM
4507456	B5KABD IP55 IK03 9W/830 GLFR ANT H	9	500
4507455	B5KABC IP55 IK03 9W/830 GLFR SI H	9	500
4507454	B5KABB IP55 IK03 9W/830 GLFR BK H	9	500
4507453	B5KABA IP55 IK03 9W/830 GLFR WH H	9	500

Kappa H 840

NO.	CODE	W	LM
4509988	B5KABH IP55 IK03 9W/840 GLFR ANT H	9	520
4509987	B5KABG IP55 IK03 9W/840 GLFR SI H	9	520
4509986	B5KABF IP55 IK03 9W/840 GLFR BK H	9	520
4509985	B5KABE IP55 IK03 9W/840 GLFR WH H	9	520

Kappa H E27

NO.	CODE
4509992	B5KABL IP55 IK03 E27 GLFR ANT H
4509991	B5KABK IP55 IK03 E27 GLFR SI H
4509990	B5KABJ IP55 IK03 E27 GLFR BK H
4509989	B5KABI IP55 IK03 E27 GLFR WH H