





Naos

Naos is a clean-lined, low-profile general luminaire range designed for offices, schools, corridors and other public spaces. The range includes three housing lengths and two housing widths. The luminaire is surface-mounted. The diffuser with a magnet attachment facilitates mounting. Wire-suspension fixtures are available for the Naos 145 mm and Naos 195 mm models to enable suspension mounting.

- Steel housing and opal acrylic diffuser (ACO).
- White RAL 9003.
- Protection class I.
- Linkable, 3/5 x 2.5 mm² Two cable lead-throughs.
- Installation height: 2–4 m.
- Fixed LED: 10–46 W / 1300–6400 lm.
- Colour temperatures: 3000 K and 4000 K. CRI > 80 / Ra > 80.
- MacAdam 3 SDCM.
- IP20.
- The standard range includes on/off and Dali-2 models.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L80 100 000 h (Ta25°C).
- Rated lifetime L90 55 000 h (Ta25 °C).
- Power source service life 50 000 h.
- Suspension mounting enabled using a wire-suspension fixture (Naos 4146970 for 145 mm luminaires or Naos 4146964 for 195 mm luminaires), available by special order.
- WH = white, DA2 = Dali-2.
- Also available as 1–10 V and Switch Dim solutions on a project-specific basis. The luminaire is also available for order with a micro-prismatic diffuser, a different frame size, and in grey (RAL 9006). The colour temperature options available are: 3000 K, 5000 K and 6500 K. CRI > 90 available by special order. Also available with various efficacies and lumen outputs of 1050–6 600.



By order

Naos

NO.	CODE		W	LM
4146826	T2NACA	620x145 IP20 10W/840 WH	10	1280
4146822	T2NACB	620x195 IP20 19W/840 WH	19	2580
4146821	T2NACC	1180x145 IP20 20W/840 WH	20	2520
4146820	T2NACD	1180x195 IP20 37W/840 WH	37	5200
4146827	T2NACE	1460x145 IP20 24W/840 WH	24	3140
4146816	T2NACF	1460x195 IP20 46W/840 WH	46	6430

Naos Dali

NO.	CODE		W	LM
4146824	T2NACA-DALI	620x145 IP20 10W/840 DA2 WH	10	1280
4146823	T2NACB-DALI	620x195 IP20 19W/840 DA2 WH	19	2580
4146825	T2NACC-DALI	1180x145 IP20 20W/840 DA2 WH	20	2520
4146819	T2NACD-DALI	1180x195 IP20 37W/840 DA2 WH	37	5200
4146818	T2NACE-DALI	1460x145 IP20 24W/840 DA2 WH	24	3140
4146817	T2NACF-DALI	1460x195 IP20 46W/840 DA2 WH	46	6430

Naos Accessories

NO.	CODE	
4146964	A2NAXB	Wire suspension Naos 195mm
4146970	A2NAXA	Wire suspension Naos 145mm