



Optimus

The low-profile Optimus IP44 luminaire is a versatile lighting solution for industrial facilities, commercial properties, warehouses, corridors and wet spaces. The product is equipped with a keyhole slot for easy installation. It can be mounted on a ceiling, a wall and on a suspension rail. The range consists of two colour temperatures and three lengths. Mounting fixtures designed for population shelters are also available for the product (A2OPKD).

- Steel body and polycarbonate diffuser.
- White.
- Protection class I.
- Surface mounting.
- 25 W: On/off.
- 45 W: On/off and Radar.
- 60 W: On/off and Radar.
- Linkable, 5 x 2.5 mm².
- Radar models are not suitable for Master/Slave installations.
- Installation height 2–6 m.
- Colour temperatures 3000 K and 4000 K.
CRI > 80 / Ra > 80.
- IP44.
- IK08.
- Fixed LED 25 W / 2500 lm, 45 W / 4500 lm, 60 W / 6000 lm.
- MacAdam 3 SDCM.
- On/off (25 W, 45 W and 60 W) and radar (45 W and 60 W).
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 60 000 h (Ta25°C).
- Rated lifetime L80 50 000 h (Ta25°C).
- Available with project-specific connecting wires.

• In stock

Optimus




NO.	CODE	W	LM
• 4310647	A3OPGA IP44 25W/830 PCO WH	25	2500
• 4310532	A2KEAA IP44 25W/840 PCO WH	25	2500
• 4310648	A3OPGB IP44 45W/830 PCO WH	45	4500
• 4310533	A2KEAB IP44 45W/840 PCO WH	45	4500
• 4310650	A3OPGD IP44 60W/830 PCO WH	60	6000
• 4310535	A2KEAD IP44 60W/840 PCO WH	60	6000

Optimus sensor luminaires

NO.	CODE	W	LM
• 4310649	A3OPGC IP44 45W/830 RA PCO WH	45	4500
• 4310534	A2KEAC IP44 45W/840 RA PCO WH	45	4500
• 4310651	A3OPGE IP44 60W/830 RA PCO WH	60	6000
• 4310536	A2KEAE IP44 60W/840 RA PCO WH	60	6000

Optimus accessories

NO.	CODE
•	A3OPAG Wall bracket 45deg WH
•	A2OPKD Shelters bracket 2 pcs



Easy installation.



Wall bracket
A3OPAG.

Shelters bracket
A2OPKD.